

BIG LUG

DUMP TRAILERS

FD SERIES DUMP TRAILER



BigLug FD delivers 3 trailers in 1. It's an equipment trailer; a dump trailer; and a flatbed trailer all rolled in one. BigLug FD offers the perfect combination of versatility, convenience, safety and it's built tough to take on a variety of jobs. Haul heavy equipment, move big pallets or oversized loads, dump materials, gravel, debris – it's all easy with BigLug FD. Featuring an 18' long dump bed, convenient drive-over fenders, plus a 3-stage hydraulic hoist that delivers an impressive 52-degree dump angle. Loaded with lots of standard equipment and plenty of options to choose from including 24" and 45" Side Kits, Gooseneck or Tag Along Hitch, Gooseneck Caddy, Spare Tire Carrier & Tire, Hydraulic Jack and Secondary Battery System. Checkout BigLug FD...one trailer for all your needs.



Custom Trailer Works
 A Division of Cubic Designs, Inc.
 1977 State Hwy 22/54 Waupaca, WI 54981
 800-242-7061
 Fax 715-256-9752
www.big-lug.com

FD SERIES SPECIFICATIONS

Models	CT1814FD	CR1814FD	
HITCH	Tag Along	Tag Along	Gooseneck
GVWR	15,760 lbs.	15,580 lbs.	17,060 lbs.
EMPTY WEIGHT	4,560 lbs.	4,760 lbs.	5,160 lbs.
PAYLOAD/DUMP CAPACITY	11,200 lbs.	11,000 lbs.	12,100 lbs.
AXLE SPECS	2 Dexter 7K	2 Dexter 7K	2 Dexter 7K
AXLE CONFIGURATION	4" Drop	4" Drop	4" Drop
ELECTRIC BRAKES	Both Axles	Both Axles	Both Axles
RIMS	8 on 6.5 Silver Mod	8 on 6.5 Silver Mod	8 on 6.5 Silver Mod
RADIAL TIRES	ST 235 80 R16E	ST 235 80 R16E	ST 235 80 R16E
TIRE RATING	3,520 lbs. Each	3,520 lbs. Each	3,520 lbs. Each
MODULAR WIRING	100% Sealed	100% Sealed	100% Sealed
12 V TRICKLE CHARGER	Yes	Yes	Yes
BREAK AWAY SYSTEM	Yes	Yes	Yes
LED LIGHTS	Yes	Yes	Yes
QUAD TAILLIGHTS	Yes	Yes	Yes
TRAILER PLUG	7 Round RV	7 Round RV	7 Round RV
DEEP CYCLE BATTERY	Yes	Yes	Yes
HYDRAULIC PUMP	Single Acting	Single Acting	Single Acting
HOIST CYLINDERS	Single 6" 3-Stage	Single 6" 3-Stage	Single 6" 3-Stage
DUMP ANGLE	52 Degrees	52 Degrees	52 Degrees
CONTROL CORD	25' Cord	25' Cord	25' Cord
BED DIMENSIONS	96"W x 18'L	96"W x 18'L	96"W x 18'L
DECK HEIGHT	27"	27"	27"
DUMP BODY FLOOR	12 ga. Floor Plate	12 ga. Floor Plate	12 ga. Floor Plate
DUMP BODY FRAME	4"x2" Rectangular Tube	4"x2" Rectangular Tube	4"x2" Rectangular Tube
CROSS MEMBERS	12" O.C.	12" O.C.	12" O.C.
FENDERS	Drive-Over 1/4" Floor Plate	Drive-Over 1/4" Floor Plate	Drive-Over 1/4" Floor Plate
RUB RAILS	Yes	Yes	Yes
D RINGS	(4) Welded in Corners	(4) Welded in Corners	(4) Welded in Corners
STAKE POCKETS	Yes	Yes	Yes
BODY PROPS	2	2	2
6' PULL OUT RAMPS	Yes	Yes	Yes
12" BULKHEAD	Yes	Yes	Yes
2 5/16" ADJ. COUPLER	Yes	Yes	Yes
BOLT-ON JACK	7K Dropleg Top Wind	12K Dropleg Side Wind	12K Dropleg Side Wind
POWDER COAT FINISH	Yes	Yes	Yes

NOTE: Options added to a base trailer will decrease the payload by an amount equal to the weight of the options added. Payload/dump capacity for CG1814FD based upon the load center of gravity being 9" forward of the bed centerline. Any FD series trailer shipped with the optional 8k axles provide an additional payload capacity of 2,300 lbs. for Tag Along models and 2,600 lbs. for Gooseneck models.